# Technical Data Sheet

## Superfast™ Violet RP

**Color Type** Quinacridone

**Color Index No.** P.V.19

**CAS NO.** 1047-16-1



### Structual



| Fastness Properties | Data |
|---|---|
| Heat Resistance（HDPE-5min，℃） | 300 |
| Fastness to weathering（Reduction） | 5 |
| Fastness to bleeding（Full shade） | 5 |
| Acid Resistance | 5 |
| Alkali Resistance | 5 |

### Description

- **High color saturation**
- **Eco-friendly and high lightfastness**
- **Stable crystal form and crystal structure**

### Application

UV INKJET
WATERBASED INKJET

### Physical Properties

| Items | Data |
|---|---|
| Density ($g/cm^3$) | 1.4-1.6 |
| Specific Surface Area（$m^2/g$） | 70 |
| Average particle size（nm） | 105 |
| Warping in HDPE | low |

### Package

10KG/Compound Bag

*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

**Gaoyou Huabao Pigment Co.,Ltd**
**Shandong Huabao Pigment Co.,Ltd**
Add: Room 1103,No.1076,Changshou RD, Putuo District,Shanghai
Tel: 86-19818298813